

DESCRIPTION.

It may be small but Centauri Minor is extremely versatile, and with a minimal aesthetic and impressive optics it will be the glowing highlight of any space. A modern lighting choice for both residential and commercial lighting applications. It can be either suspended as a pendant, to provide both down and up lighting, or easily surface mounted.


FEATURES.

- A wide distribution designed to illuminate task surfaces
- Dot-free homogeneous illumination
- Optional ultra-wide upward indirect light
- A seamless system creating up to 30 metre single lengths
- Customisable finishes available
- Low glare diffuser able to achieve UGR 19 up to 2500lm



DIMENSIONS.

Suspended



TECHNICAL DATA.

APPLICATIONS	Commercial and residential lighting
INSTALLATION	Interior
MOUNTING	Suspended
MATERIALS	Extruded Aluminium Body, Continuous diffuser and Aluminium End caps
OPTIC	Opal Low Glare
LIGHT SOURCE	LED Boards
EFFICIENCY	Low Glare: up to 94.4 lm/W Opal: up to 108.1 lm/W
COLOUR TEMP	3000K 4000K Beyond Vision
DIMENSIONS	W 62mm x H 90mm
CONTROL	Non Dim DALI Casambi
WARRANTY	10 Year Product Warranty & 13 Months Labour Warranty
FINISH	Black or White powder-coat Custom colours available



* Beyond Vision only available with CRI80+
 # Tuneble available as a custom option

LUMINAIRE SELECTION.



MOUNT	FINISH	LENGTH	LIGHT SOURCE	OPTIC	LUMENS	CRI	CCT	IP RATING	DIM	INDIRECT LUMENS	INDIRECT CRI	INDIRECT CCT
SP <i>Suspended</i>	BL <i>Black</i>		DT <i>Direct</i>	OP <i>Opal</i>	Refer to lumen tables below lm	8 80+	30 3000K	IP20	ET <i>Non-Dim</i>	Refer to lumen tables below lm	8 80+	30 3000K
	WH <i>White</i>	Length mm	DI <i>Direct & Indirect*</i>	LG <i>Low Glare</i>		9 90+	40 4000K		DA <i>DALI</i>		9 90+	40 4000K
	CS <i>Custom</i>						TW# <i>Tuneable</i>	CA <i>Casambi</i>	8 80+		BV <i>Beyond Vision</i>	

DIRECT EXAMPLE:



INDIRECT EXAMPLE:



LUMEN TABLES.

OPAL DIRECT

	CR180 3000K/4000K	CR190 3000K/4000K	Beyond Vision
1000lm	9.5W/m	10.6W/m	
1500lm	15.0W/m	16.2W/m	
2000lm	19.7W/m	22.0W/m	21.2W/m
2500lm	23.4W/m	27.8W/m	26.5W/m
3000lm	27.8W/m	32.4W/m	31.8W/m
3500lm	32.4W/m	39.3W/m	37.1W/m

LOW GLARE DIRECT

	CR180 3000K/4000K	CR190 3000K/4000K	Beyond Vision
1000lm	10.6W/m	12.8W/m	
1500lm	16.2W/m	20.9W/m	
2000lm	22W/m	25.6W/m	26.5W/m
2500lm	27.8W/m	32.4W/m	31.8W/m
3000lm	32.4W/m	39.3W/m	37.1W/m
3500lm	39.3W/m		45.0W/m

These outputs are quoting luminaire outputs per metre. Actual lumen output may vary by +/- 10% depending upon colour temperature. Check IES files for exact output.

INDIRECT WIDE BEAM

	CR180 3000K/4000K	CR190 3000K/4000K	Beyond Vision
1000lm	7.3W/m	8.4W/m	
1500lm	10.6W/m	12.8W/m	
2000lm	15W/m	17.3W/m	
2500lm	16.7W/m	21.1W/m	21.2W/m
3000lm	21.1W/m	25.6W/m	26.5W/m
3500lm	25.6W/m	30.1W/m	29.1W/m

Minor

SUSPENDED

centauri



www.centauri.lighting

Actual product characteristics may vary. Centauri and Light Culture reserves the right to improve, modify or update the product designs without prior notice.

lightculture)
INSPIRED LIGHT